

AMENDMENTS TO THE CLAIMS

This Listing of Claims will replace all prior versions, and listings, of claims in this application:

Listing of Claims:

1. (Previously Presented) A needle device comprising:
 - a housing having a base for placement against a surface of a needle penetrating site, the base including a first opening;
 - a needle mounted for a movement between a retracted position in the housing and an extended position, a portion of the needle extending through the first opening in the extended position;
 - an actuator movably mounted to the housing and movable between an unactuated position in which the needle is in the retracted position and an actuated position in which the needle is in the extended position; and
 - a retraction mechanism that automatically moves the needle to the retracted position responsive to releasing the base from the site surface.
2. (Original) A needle device according to Claim 1, wherein the needle is biased toward a retracted position.
3. (Previously Presented) A needle device according to Claim 2 , wherein the retraction mechanism maintains the needle in the retracted position upon moving the

actuator to the actuated position.

4. (Original) A needle device according to Claim 1, wherein the retraction mechanism includes a trigger member movably mounted to the housing, the trigger member having a first portion adapted to engage the actuator and a second portion adapted to contact the site surface.
5. (Original) A needle device according to Claim 4, wherein the trigger member is pivotally mounted to the housing.
6. (Original) A needle device according to Claim 5, wherein the base further includes a second opening through which the second portion of the trigger member is adapted to contact the site surface.
7. (Original) A needle device according to Claim 4, wherein the housing has an actuator guide that guides the actuator through a predetermined path of movement.
8. (Original) A needle device according to Claim 7, wherein the guide comprises a substantially U-shaped channel formed in the housing, the U-shaped channel comprising a first substantially vertical guide portion, a second substantially vertical guide portion and a horizontal guide portion connecting lower ends of the first and second vertical portions.
9. (Original) A needle device according to Claim 8, wherein the actuator is rotatably

and vertically movable mounted to the housing, and further includes a pin adapted to be guided in the U-shaped channel.

10. (Original) A needle device according to Claim 9, further including a spring that biases the actuator to the unactuated position the spring having one end thereof fixedly mounted to the actuator and another end thereof fixedly mounted to the base to enable creation of a spring torsional load when the actuator is rotated relative to the base.

11. (Original) A needle device according to Claim 10, wherein the spring is torsionally preloaded to rotate the actuator from the first vertical guide portion to the second vertical guide portion through the horizontal guide portion upon moving the actuator to the actuated position.

12. (Canceled)

13. (Previously Presented) A needle device according to Claim 11, wherein the trigger member is pivotally mounted to the housing and the first portion thereof is adapted to engage the pin and prevent the actuator from moving to the unactuated position when the pin is positioned in the second vertical guide portion and the second portion thereof is contacting the site surface.

14. (Original) A needle device according to Claim 13, wherein the base further includes a second opening through which the second portion of the trigger member is

adapted to contact the site surface.

15. (Original) A needle device according to Claim 14, wherein the actuator guide further includes a lock portion contiguous with the second vertical guide portion.

16. (Original) A needle device according to Claim 15, wherein the spring torsional preloading further rotates the actuator into the lock portion to lock the actuator from moving to the actuated position.

17-27. (Canceled)

28. (Previously Presented) A needle device comprising:

a housing having a base adapted to be placed next to a surface of a needle-penetrating site, the base including an opening;

a needle mounted for a movement between a retracted position in the housing and an extended position, where a portion of the needle extends through the opening when in the extended position;

an actuator movably mounted to the housing and movable between an unactuated position at which the needle is in the retracted position and an actuated

position at which the needle is in the extended position, the actuator being biased toward the unactuated position;

a retraction mechanism that automatically moves the needle from the extended position to the retracted position, the retraction mechanism being configured to begin

SYNNESTVEDT & LECHNER LLP

moving the needle to the retracted position in response to removal of the needle device from the surface.

29. (Original) A needle device according to Claim 28, further comprising a locking mechanism that prevents the needle from moving back to the extended position once the needle has been moved from the extended position to the retracted position.

30. (Original) A needle device according to Claim 29, wherein the locking mechanism is integral with the retraction mechanism.

31. (Previously Presented) A needle device according to Claim 28, wherein the retraction mechanism includes a cover member for covering the opening after a tip of the needle moves from the extended position to the retracted position, in which the tip of the needle is received within the housing.

32-53. (Canceled)